

# TV98Q

<b>CPU</b>	Allwinner H313 Quad Core ARM Cortex A53	
<b>GPU</b>	G31 OPenGL3.2	
<b>Memory</b>	DDR3: <b>2GB (Option:1GB)</b>	
<b>Flash</b>	eMMC: <b>16GB (Option:8GB )</b>	
<b>WiFi</b>	IEEE 802.11 b/g/n	
<b>Moudle</b>	Plastic : Black Color	
<b>I/O</b>	1*HDMI	4K*2K UHD Output, <b>HDMI 2.0A</b>
	1*AV OUT	480i/576i standard definition output
	2*USB	1* USB Host Port ,1*USB Device
	1*IR Reciver	Remote Reciver Connect
	1*RJ45	Ethernet Interface
	1*TF CARD	Support 4GB/8GB/16GB/32GB/64GB
<b>Power</b>	DC 5V/2A; LED indicator, <b>Working : Blue; Standby: Red</b>	
<b>Software</b>		
<b>OS</b>	<b>Android 10.0 update to 12.1</b>	
<b>Video</b>	Amlogic Video Engine (AVE) with dedicated hardware decoders and encoders Support multi-video decoder up to 4K@60fps Supports multiple "secured" video decoding sessions and simultaneous decoding and encoding Video/Picture Decoding - VP9 Profile-2 up to 4K@30fps - H.265 Main10@L5.1 up to 4K@60fps - AVS2 JiZhun 10bit Profile up to 4K@60fps - H.264 BP/MP/HP@L4.2 up to 4K@30fps - H.263 BP up to 1080P@60fps - MPEG-4 SP/ASP@L5 up to 1080P@60fps - MPEG-2 MP/HL up to 1080P@60fps - MPEG-1 MP/HL up to 1080P@60fps - Xvid up to 1080P@60fps - Sorenson Spark up to 1080P@60fps - VP8 up to 1080P@60fps - AVS/AVS+ JiZhun Profile up to 1080P@60fps - WMV9/VC1 SP/MP/AP up to 1080P@60fps - JPEG HFIF file format up to 45M PPS - Multiple language and multiple format sub-title video support - MJPEG and JPEG unlimited pixel resolution decoding (ISO/IEC-10918)	
	<b>Audio</b>	
<b>Audio</b>	Supports MP3, AAC, WMA, RM, FLAC, Ogg and programmable with 7.1/5.1 down-mixing Built-in serial digital audio SPDIF/IEC958 input/output and PCM input/output • Two DAC channels • Supports 1 audio output interface (differential LINEOUTP/N or single-end LINEOUTL/LINEOUTR) • One Audio HUB, supporting internal mixing function • Embedded 3 I2S/PCM (I2S0 for extended audio codec, I2S2 for BT, I2S3 for digital power amplifier) • Supports Left-justified, Right-justified, Standard I2S mode, PCM mode, and TDM mode • I2S mode supports 8 channels, and 32-bit/192kbit sample rate • I2S and TDM modes support maximum 16 channels, and 32-bit/96kbit sample rate • One OWA OUT interface, supporting 16-/20-/24-bit inputs and outputs • Integrated digital microphone(DMIC), supporting maximum 8 digital PDM microphones	
<b>Image</b>	HD JPEG、BMP、GIF、PNG、TIF	
<b>Language</b>	English French German Spanish Italian etc multilateral languages	
<b>Appliactions</b>		
<b>Online</b>	Browse all video websites,support Netflix,Hulu,Flixster, Youtube, etc.	
<b>Apps</b>	Apps download freely form android market、amazon app store etc.	
<b>Medium</b>	Local Media playback,Support HDD, U Disck ,TF Card .	
<b>Talk online</b>	Support SKYPE video call ,MSN , facebook ,twitter ,QQ etc	
<b>Others</b>	Support Email,office suit etc.	
<b>Packing</b>	Product dimension	88.4*88.4*18.6(mm)
	Qty per unit packing	1pcs
	Unit packing: (LxWxH)	170*115*55(mm)
	Unit packing (G.W.)	0.35Kg
	Qty per export carton	20PCS
	Export carton (WxHxL)	370*290*240 (mm)
	Export carton (G.W.)	7.5Kg
<b>Accessories :</b>		
1、HDMI cable *1		
2、IR Remote *1		
3、User Manual *1		
4、Package box *1		
5、Power adapter *1		